

# DALA°PRO®FIL AB

Kulör:

## LAGERSTANDARD 2018-11-01

Tjocklek (mm) / Beläggning	0502-Y (0,20)	001 010 015 022	036 044 045 087	113 145 181 244	387 418 434 461	502 524 558 742	758 762 874 **	Endas t t Prime	Alu-zink Z 275 350	Z 4301 44xx	1. 3103-H16
0,5 Polyester	X X X			X X X		X X X					
0,55 GreenCoat Crown	X X										
0,6 Polyester	X X										
0,7 Polyester	X X										
0,5 Polyester Perforerad	X X										
0,6 Plastisol 200µ	X							X			
0,6 GreenCoat Crown	X X			X X X		X X X					
0,6 GreenCoat Pro BT DX51D (FA)	X X			X X X		X X X					
0,6 GreenCoat Pro BT DX54D (PLX)	X X			X X X		X X X					
0,6 Matt GreenCoat Pro BT DX51D (FA)	X X			X X X		X X X					
0,6 Matt GreenCoat Pro BT DX54D (PLX)	X X			X X X		X X X					
1,0 High Build DX51D (FA)	X X										
0,6 PVF <sub>2</sub>				X							
0,4 Aluzink AZ185						X					
0,5 Aluzink AZ185 DX51D (FA)						X					
0,6 Aluzink AZ185 DX51D (FA)						X					
0,6 Aluzink AZ185 DX54D (PLX)						X					
0,6 Galv Z350 DX54D (PLX)							X				
0,7/0,9/1,25/1,5 Galv Z775 DX51D (FA)								X			
0,5 Rostfri Blank 2B									X		
0,5 Syrafast Blank 2B									X		
0,5 Syrafast AN 5									X		
0,7 Aluminium Blank, Stucco										X	
0,9 Aluminium											
0,6 Kulturplåt Z350 DX54D (PLX)										X	

FA, PLX Trademarks by SSAB

Reservation för mellanförslagning